


Suspension Enhancement FORD F250/350 4x4 [1999-2004] SumoSprings Part# SSF-103-40









Refer to SumoSprings application guide for part selection www.supersprings.com [Tech line #866-898-0720]
SumoSprings enhance load carrying capability, handling & towing. Never exceed vehicle manufacturer's GVWR rating.

Installation Instructions

- 1) Park vehicle on level hard surface. Engage emergency brake. Place blocks in front and behind rear wheels to prevent rolling. Observe all safety precautions and wear safety glasses.
- 2) Raise front of vehicle allowing the axle to hang freely. Support the frame using safety jack stands.
- 3) Remove existing factory jounce bumper assembly by unbolting the two hex nuts and removing the assembly.
- 4) Attach the SumoSpring by threading the two studs of the assembly through the existing holes in the underside of the frame from which the factory jounce bumper assembly was removed.
- 5) Install the supplied flat washers and nuts on top of the studs and tighten securely.
- 6) Repeat steps three through five on the other side of the vehicle.
- 7) Jack up vehicle, remove safety jack stands.
- 8) Carefully lower vehicle to the hard surface. Remove the blocks in front and back of the rear wheels.
- 9) Release emergency brake.
- 10) Fill out warranty card and send to SuperSprings. The warranty card is on the reverse side of this page.

| | <u>Tool List</u> | | | <u>Parts List</u> | |
|---|--------------------|---|---|-------------------|---|
| • | Floor Jack | 1 | • | SumoSprings | 2 |
| • | Jack Stands | 2 | • | M8 Washers | 4 |
| • | 13mm Socket/Wrench | 1 | • | M8 Nuts | 4 |
| • | Ratchet | 1 | | | |
| | Wheel Blocks | Δ | | | |

Important Notice.

- 1) For easy installation please read instructions completely first and have all necessary tools available.
- 2) We recommend that this installation be done by a professional or persons with sound mechanical knowledge.
- 3) SumoSprings are designed to work with the original factory springs only. If they have been replaced with aftermarket springs then please consult with Supersprings International at 866-898-0720.
- 4) These instructions are meant as a guide for the installation of SumoSprings. SuperSprings International assumes no liability for the actual installation process. Installers should apply common automotive safety practices when raising, lowering and working on vehicles.
- 5) SumoSprings are designed to enhance the vehicles load carrying performance and road handling however it does not authorize (or recommend) loading beyond the manufacturer's GVWR specifications.
- 6) For technical support contact SuperSprings International at 866-898-0720.

To prevent damage to the vehicle and to ensure safety, do not exceed the maximum load recommended by the vehicles manufacturer (GVWR).